BE POWER EQUIPMENT

BEPOWEREQUIPMENT.COM

# 10,500 PEAK WATTS TRI-FUEL INVERTER GENERATOR

COMMERCIAL SERIES

MODEL: BE10500iT

## FEATURES

- **Quiet and powerful inverter** capable of performing many tasks. Especially popular for camping.
- **Produces clean energy** that is needed for sensitive electronics like cell phones and computers.
- **Rugged and reliable engine** with automatic low oil-shutdown that safeguards the engine.
- **Copper alternator windings** increases efficiency and reduces heat build up to extend lifespan.
- **Easy access outlets** are protected by circuit breakers for safety.
- **Sound dampening shell** lowers volume and has easy access panels to keep maintenance simple.
- **Weather-protected outlets** ensures reliable power access during all weather conditions.
- **LED floodlight** provides powerful and reliable illumination.
- **Sub-Zero technology** allows the engine to start in cold weather conditions.
- **CO2 detector** automatically shuts down the generator before harmful levels of carbon monoxide accumulate.

Scan the QR code with your mobile device and discover more about this BE Digital Inverter.

TRI-FUEL




PLUG TYPES

## ENGINE

| | |
|---|---|
| MODEL: | **POWEREASE 458CC** |
| TYPE: | **AIR COOLED, 4-STROKE OHV** |
| DISPLACEMENT: | **458CC** |
| DB RATING: | **64dB @ 7M** |
| ECO MODE: | **YES** |
| START TYPE: | **ELECTRIC/RECOIL** |
| FUEL TYPE: | **86 OCTANE, UP TO 10% ETHANOL** |
| FUEL TANK SIZE: | **26L (6.8 GAL)** |
| APPROX RUN TIME: | **9HR @ 1/2 LOAD** |
| OIL TYPE: | **SAE 10W30** |
| CERTIFICATIONS: | **ETL, EPA** |

## FRAME

| | |
|---|---|
| TYPE: | **ENCLOSED PLASTIC SHELL** |
| PORTABILITY: | **FOLDING HANDLES** |
| WHEELS: | **YES** |

## ALTERNATOR

| | |
|---|---|
| MAX WATT (GAS/LPG/NG): | **10,500/9,500/8,400 W** |
| RUNNING WATT: (GAS/LPG/NG): | **8,500/8,000/6,800 W** |
| MASTER CIRCUIT BREAKER: | **71A @ 120V**<br>**35.5A @ 240V** |
| VOLTAGES: | **120V/240V** |
| WINDINGS: | **COPPER** |
| HARMONIC DISTORTION: | **MAX ≤ 3%** |
| GROUNDING: | **NEUTRAL BONDED** |

## OUTLETS

2x DUPLEX 20A 120V (L5-20R) GFCI
1x 12V AUXILIARY
1x 120V/240V TWIST (L14-30R)
1x 50A DRYER PLUG (L14-50R)

## BOXED SIZE

| | |
|---|---|
| LxWxH: | **37"x 25"x 32"** |
| WEIGHT: | **297 LBS** |

## UNIT SIZE

UNIT WEIGHT: **238 LBS**

## WARRANTY

| | |
|---|---|
| ENGINE BASIC: | **2 YEARS** |
| ENGINE REGISTERED: | **5 YEARS** |
| ELECTRONICS: | **1 YEAR** |
| UPC: | **777987383715** |

11-2023

**THE POWER YOU NEED.**

POWEREASE

BE POWER EQUIPMENT

BEPOWEREQUIPMENT.COM

# GÉNÉRATRICE ONDULEUR 10 500 WATTS

MODÈLE: BE10500iT

COMMERCIAL SERIES

## CARACTÉRISTIQUES

- **Onduleur ultra-puissant et silencieux** capable de performer plusieurs applications. Spécialement populaire en camping.
- **Produit de l'énergie** propre nécessaire aux appareils électroniques sensibles tel que cellulaires et ordinateurs.
- **Moteur robuste et fiable** avec arrêt niveau bas niveau d'huile automatique le gardant en sécurité.
- **Enroulements d'alternateur** en cuivre augmentant l'efficacité et réduisant la chaleur accumulée prolongeant la longévité.
- **Sorties facile d'accès** protégées par des disjoncteurs pour la sécurité.
- **Coquilles insonorisantes réduisant** le volume et avec des panneaux facile d'accès facilitant l'entretien.
- **Sorties protégées des intempéries** assurant un accès fiable à l'électricité dans toutes conditions météorologiques.
- **Le projecteur LED** fournit un éclairage puissant et fiable.
- **La technologie Sub-Zero** permet au moteur de démarrer par temps froid.
- **Le détecteur automatique de CO** arrête la génératrice avant que des niveaux nocifs de monoxide de carbone ne s'accumulent.

Scannez le code QR avec votre cellulaire et apprenez-en plus à propos de cette génératrice BE.

**TRI-CARBURANT**




**PLUG TYPES**

## MOTEUR

| | |
|---|---|
| MODÈLE: | **POWEREASE 458CM³** |
| TYPE: | **REFROIDISSEMENT PAR AIR, 4-TEMPS OHV** |
| DISPLACEMENT: | **458CM³** |
| TAUX DB: | **64dB @ 7M** |
| MODE ÉCO: | **OUI** |

TYPE DE DÉMARRAGE: **MANUEL / ÉLECTRIQUE**
TYPE D'ESSENCE: **86 OCTANE, JUSQU'À 10% ETHANOL**
TAILLE DU RÉSERVOIR DE CARBURANT: **26L (6,8 GAL)**
TEMPS APPROX. EN MARCHE: **9HR @ 1/2 LOAD**

| | |
|---|---|
| TYPE D'HUILE: | **SAE 10W30** |
| CERTIFICATIONS: | **ETL, EPA** |

## CHÂSSIS

| | |
|---|---|
| TYPE: | **COQUE EN PLASTIQUE FERMÉE** |
| PORTABILITÉ: | **POIGNÉE DE TRANSPORT** |
| ROUES: | **OUI** |

## ALTERNATEUR

| | |
|---|---|
| WATTS AU DÉMARRAGE (GAZ / GPL / NG): | **10 500 W / 9 500 W / 8 400 W** |
| WATTS CONTINUE (GAZ / GPL / NG): | **8 500 W / 8 000 W / 6 800W** |
| DISJONCTEUR PRINCIPAL: | **71A @ 120V 35,5A @ 240V** |
| TENSIONS: | **120V / 240V** |
| ENROULEMENTS: | **CUIVRE** |
| DISTORSION HARMONIQUE: | **MAX ≤ 3%** |
| MISE À LA TERRE: | **NEUTRE LIÉ** |

## PRISES ÉLECTRIQUES

2x PRISES DUPLEX 20A 120V (L5-20R) GFCI
1x SORTIE AUXILIAIRE DC 12V
1x VERROU TOURNANT 30A 120V/240V (L14-30R)
1x PRISE DE SÉCHEUSE 50A (L14-50R)

## TAILLE DE LA BOÎTE

| | |
|---|---|
| LxWxH: | **37"x25"x32"** |
| POIDS: | **297 LBS** |

## TAILLE DE L'UNITÉ

POIDS DE L'APPAREIL: **238 LBS**

## GARANTIE

| | |
|---|---|
| MOTEUR DE BASE: | **2 ANS** |
| MOTEUR ENREGISTRÉ: | **5 ANS** |
| ÉLECTRONIQUES: | **1 AN** |
| UPC: | **777987383715** |

11-2023

**LA PUISSANCE DONT VOUS AVEZ BESOIN.**

POWEREASE