



## Material Safety Data Sheet

### 1. Material and company identification

**Material Name** : Rotair Plus  
**Product Use** : Compressor oil  
**Product Code** : 0017 1398 15  
**Manufacturer/Supplier** : ICD (International Compressor Distribution) nv,  
Boomssteenweg 957,  
2610 Wilrijk, Belgium  
**Telephone** : Please contact your local Service Center or the ICD office in Belgium:  
+32 3 870 2111 (8am-5pm CET)  
**Email Contact for Safety Data Sheet** : If you have any enquiries about the content of this Material Safety Data  
Sheet please email [info.lubricants@icdcompany.com](mailto:info.lubricants@icdcompany.com)  
**Emergency Telephone Number** : Only for medical related issues, please contact CHEMTREC: 800-424-  
9300

### 2. Hazards identification

**2.1 GHS Classification** : Not a hazardous substance or mixture.  
**GHS Label element**  
**Hazard pictograms** : No Hazard Symbol required  
**Signal word** : No signal word  
**2.2 Hazard statements** : **PHYSICAL HAZARDS:**  
Not classified as a physical hazard under GHS criteria.  
**HEALTH HAZARDS:**  
Not classified as a health hazard under GHS criteria.  
**ENVIRONMENTAL HAZARDS:**  
Not classified as an environmental hazard under GHS criteria.  
**2.3 Precautionary statements**  
**Prevention** : No precautionary phrases.  
**Response** : No precautionary phrases.  
**Storage** : No precautionary phrases.  
**Disposal** : No precautionary phrases.  
**Other hazards which do not result in classification** : Prolonged or repeated skin contact without proper cleaning can clog  
the pores of the skin resulting in disorders such as oil acne/folliculitis.  
Used oil may contain harmful impurities.  
Not classified as flammable but will burn.  
The classification of this material is based on OSHA HCS 2012 criteria.  
Under normal conditions of use or in a foreseeable emergency, this  
product does not meet the definition of a hazardous chemical when  
evaluated according to the OSHA Hazard Communication Standard,  
29 CFR 1910.1200.



## Material Safety Data Sheet

### 3. Composition/information on ingredients

- 3.1 Chemical nature** : Highly refined mineral oils and additives.  
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.  
\* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9.

### 3.2 Hazardous components

Chemical Name	Synonyms	CAS-No.	Concentration (%)
Interchangeable low vis-cosity base oil (<20,5 cSt @40°C) *		Not Assigned	0- 90

### 4. First-aid measures

- 4.1 General advice** : Not expected to be a health hazard when used under normal conditions.
- If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
- In case of skin contact** : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
- 4.2 Most important symptoms and effects, both acute and delayed** : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- 4.3 Immediate medical attention, special treatment** : Treat symptomatically.



## Material Safety Data Sheet

### 5. Fire-fighting measures

#### 5.1 Suitable extinguishing media

: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

#### 5.2 Unsuitable extinguishing media

: Do not use water in a jet.

#### 5.3 Specific hazards during fire-fighting

: Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

#### 5.4 Specific extinguishing methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### 5.5 Special protective equipment for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

### 6. Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

: Avoid contact with skin and eyes.

#### 6.2 Environmental precautions

: Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.  
: Local authorities should be advised if significant spillages cannot be contained.

#### 6.3 Methods and materials for containment and cleaning up

: Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Additional advice : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.



## Material Safety Data Sheet

### 7. Handling and storage

- 7.1 Technical measures** : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

**Precautions for safe handling**

- : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Avoidance of contact** : Strong oxidising agents.
- Product Transfer** : This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.

### 7.2 Storage

- Other data** : Keep container tightly closed and in a cool, well-ventilated place.  
Use properly labeled and closable containers.  
Store at ambient temperature.
- Packaging material** : Suitable material: For containers or container linings, use mild steel or high density polyethylene.  
Unsuitable material: PVC.
- Container Advice** : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

### 8. Exposure controls/personal protection

#### 8.1 Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration
Oil mist, mineral	Not Assigned	TWA ((inhal-able frac-tion)	5 mg/m <sup>3</sup>
		(Mist)	5 mg/m <sup>3</sup>

**Biological occupational exposure limits**

- : No biological limit allocated.

- 8.2 Monitoring Methods** : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure con-trols. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and sam-ples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or con-tact the supplier. Further national methods may be available.



## Material Safety Data Sheet

National Institute of Occupational Safety and Health (NIOSH),  
USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA:  
Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the  
Determination of Hazardous Substances  
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen  
Unfallversicherung (IFA), Germany.  
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France  
<http://www.inrs.fr/accueil>

### 8.3 Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:  
Adequate ventilation to control airborne concentrations.  
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

### 8.4 General Information

: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard con-taminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

### 8.5 Personal protective equipment Respiratory protection

: No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].



## Material Safety Data Sheet

### 8.6 Hand protection

- Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
- For continuous contact we recommend gloves with break-through time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
- Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
- Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
- Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers..
- Environmental exposure controls
- General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour

## 9. Physical and chemical properties

- 9.1 Appearance : Liquid at room temperature.  
Colour : light brown  
Odor : Slight hydrocarbon.  
Odour Threshold : Data not available  
pH : Not applicable.  
pour point : -33 °C / -27 °F Method: ASTM D97  
Initial Boiling Point and Boiling Range : > 280 °C / 536 °F estimated value(s)



## Material Safety Data Sheet

Flash point	:	230 °C / 446 °F Method: ASTM D92
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	
	:	Data not available
Upper Explosion limits	:	
	:	Typical 1 - 10 %(V)
Lower explosion limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa at 20 °C / 68 °F (estimated value(s))
Relative vapour density	:	
	:	> 1estimated value(s)
Relative density	:	0.875 at 15 °C / 59 °F
Density	:	875 kg/m <sup>3</sup> (15.0 °C / 59.0 °F) Method: ASTM D1298
Water solubility	:	Negligible.
Solubility in other solvents	:	
	:	Data not available
Partition coefficient: n-octanol/water	:	
	:	Pow: > 6(based on information on similar products)
Auto-ignition temperature	:	
	:	>320 °C / 608 °F
Viscosity	:	
Viscosity, dynamic	:	Data not available
Viscosity, kinematic	:	6.9 mm <sup>2</sup> /s (100 °C / 212 °F) Method: ASTM D445 46 mm <sup>2</sup> /s (40.0 °C / 104.0 °F) Method: ASTM D445
Conductivity	:	This material is not expected to be a static accumulator.
Decomposition temperature	:	
	:	Data not available

### 10. Stability and reactivity

- 10.1 Reactivity** : The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
- 10.2 Chemical stability** : Stable.
- 10.3 Possibility of hazardous reactions**  
: Reacts with strong oxidising agents.
- 10.4 Conditions to avoid** : Extremes of temperature and direct sunlight.
- 10.5 Incompatible materials**  
: Strong oxidising agents.
- 10.6 Hazardous decomposition products**  
: Hazardous decomposition products are not expected to form during normal storage.



## Material Safety Data Sheet

### 11. Toxicological information

#### 11.1 Basis for Assessment

: Information given is based on data on the components and the toxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

#### 11.2 Information on likely routes of exposure

: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

##### Acute toxicity

**Product** : Expected to be of low toxicity: LD50 > 5000 mg/kg ,Rat  
Acute oral toxicity : LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:  
Acute Inhalation Toxicity : Remarks: Not considered to be an inhalation hazard under normal conditions of use.  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Expected to be of low toxicity:

#### 11.3 Skin corrosion/irritation

**Product**  
Remarks : Expected to be slightly irritating, Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

##### Serious eye damage/eye irritation

**Product**  
Remarks : Expected to be slightly irritating.

##### Respiratory or skin sensitisation

**Product**  
Remarks : Not expected to be a skin sensitiser.

##### Germ cell mutagenicity

**Product**  
Remarks : Not considered a mutagenic hazard.

#### 11.4 Carcinogenicity

**Product**  
Remarks : Not expected to be carcinogenic.  
Remarks : Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).  
**IARC** : No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.  
**ACGIH** : No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.





## Material Safety Data Sheet

**OSHA** : No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP** : No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

#### Product

Remarks : Not expected to impair fertility, Not expected to be a developmental toxicant

### STOT - single exposure

#### Product

Remarks : Not expected to be a hazard.

### STOT - repeated exposure

#### Product

Remarks : Not expected to be a hazard.

### Aspiration toxicity

#### Product

Remarks : Not considered an aspiration hazard.

## 11.5 Further information

### Product

Remarks : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

## 12. Ecological information

### Basis for assessment

: Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

## 12.1 Ecotoxicity

### Product

Toxicity to fish (Acute toxicity)

: Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity)

: Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to algae (Acute toxicity)

: Remarks: Expected to be practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity)

: Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

: Remarks: Data not available



## Material Safety Data Sheet

Toxicity to bacteria (Acute toxicity)

: Remarks: Data not available

### 12.2 Persistence and degradability

#### Product

Biodegradability : Remarks: Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but contains components that may persist in the environment.

#### Bioaccumulative potential

#### Product

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

#### Mobility in soil

#### Product

Mobility : Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

### 12.3 Other adverse effects

: no data available

#### Product

Additional ecological information

: Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Poorly soluble mixture. May cause physical fouling of aquatic organisms.

Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

## 13. Disposal considerations

### 13.1 Disposal methods

Waste from residues : Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Waste, spills or used product is dangerous waste.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

### 13.2 Contaminated packaging

: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.



## Material Safety Data Sheet

### 14. Transport information

#### National Regulations

##### US Department of Transportation Classification (49 CFR Parts 171-180)

: Not regulated as a dangerous good

#### International Regulation

IATA-DGR : Not regulated as a dangerous good

IMDG-Code : Not regulated as a dangerous good

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category : Not applicable

Ship type : Not applicable

Product name : Not applicable

Special precautions : Not applicable

#### Special precautions for user

Remarks : Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### Additional Information

: MARPOL Annex 1 rules apply for bulk shipments by sea.

### 15. Regulatory information

15.1 OSHA Hazards : No OSHA Hazards

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene, Mixed Isomers	1330-20-7	100	*
Naphthalene	91-20-3	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

##### CERCLA Reportable Quantity

: Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA, The components with RQs are given for information.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

: This material does not contain any components with a section 304 EHS RQ.

##### SARA 311/312 Hazards

: No SARA Hazards

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



## Material Safety Data Sheet

### 16. Other information

- 16.1 Further information** :
- NFPA Rating (Health, Fire, Reac-tivity) 0, 1, 0
  - : Due to the conversion of this product to GHS classification and labelling, there has been a significant change to the nature of the information presented in chapter 2. A vertical bar (!) in the left margin indicates an amendment from the previous version.
- 16.2 Abbreviations and Acronyms**
- : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
- ACGIH = American Conference of Governmental Industrial Hygienists  
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road  
AICS = Australian Inventory of Chemical Substances  
ASTM = American Society for Testing and Materials  
BEL = Biological exposure limits  
BTEX = Benzene, Toluene, Ethylbenzene, Xylenes  
CAS = Chemical Abstracts Service  
CEFIC = European Chemical Industry Council  
CLP = Classification Packaging and Labelling  
COC = Cleveland Open-Cup  
DIN = Deutsches Institut für Normung  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
DSL = Canada Domestic Substance List  
EC = European Commission  
EC50 = Effective Concentration fifty  
ECETOC = European Center on Ecotoxicology and Toxicology of Chemicals  
ECHA = European Chemicals Agency  
EINECS = The European Inventory of Existing Commercial Chemical Substances  
EL50 = Effective Loading fifty  
ENCS = Japanese Existing and New Chemical Substances Inventory  
EWC = European Waste Code  
GHS = Globally Harmonised System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IC50 = Inhibitory Concentration fifty  
IL50 = Inhibitory Level fifty  
IMDG = International Maritime Dangerous Goods  
INV = Chinese Chemicals Inventory  
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables  
KECI = Korea Existing Chemicals Inventory  
LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.



## Material Safety Data Sheet

---

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE\_HPVS = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of Chemicals

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail

SKIN\_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

**16.3 SDS Effective Date** : 01.06.2015

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

PCOILAND  
COMPRESSOR  
Experience You Can Trust  
800-542-8888